

New!

Patented One Piece Compression Connectors for Solid Center Mini Coax



FS1RCA FS1BNC FS15RCA FS15BNC

Introducing ICM's One Piece BNC and RCA compression connectors for solid center mini coax, high-end audio/video wiring and installation.

Convenient One Piece Compression Connectors...

- One Piece compression connectors allow for quick and easy installations with no separate parts. **Saves time and money in training, and reduces installer error.**
- Installers get **consistent, repeatable installations time after time.**
- Our stringent testing standards demonstrate **superior return loss numbers on our One Piece connectors.**
- Our **patented 360° compression rings on all our connectors provide TRUE 360° compression.** Ensure a quality signal with a permanent connection, **eliminating future trouble spots because of poor connection quality.**

In a Complete System....

- ICM incorporates all necessary parts and CablePro tools into a complete system for each step of the installation process, **reducing costly errors and training time.**

Patented Non-Blind Entry...

- ICM's **patented floating pin and non-blind entry design allow installers to see when the wire is set in the pin before compression.** The floating pin moves up independently as the wire is inserted, indicating proper positioning of the center pin. Non-blind entry lets installers see the wire entering the pin at the base of the connector, **ensuring a solid, secure connection every time. No guesswork involved.**

Highest Quality Products and Manufacturing...

- ICM uses the **highest quality materials and metals on the market utilizing our proprietary manufacturing process.** There's **no cracking or snapping of connectors during compression** to ensure a permanent 360° compression right from the start.

Technical Specifications:

- 75 Ohm Construction
- Brass Body Material
- Nickel/Gold Plating Material
- Brass Center Contact Construction
- Nickel Center Contact (plating)
- Cable Pullout Force Exceeding 50 in/lbs.
- Center Conductor min .015—max .025
- Dielectric min .095—max .105
- Outer Jacket min .145—max .160

One-Piece for F, BNC and RCA

- FS15RCA—Nickel RCA size 15
- RG15RCA—Gold RCA size 15
- FS15BNC—Nickel BNC size 15
- RG15BNC—Gold BNC size 15
- FS1RCA—Nickel RCA size 1
- RG1RCA—Gold RCA size 1
- FS1BNC—Nickel BNC size 1
- RG1BNC—Gold BNC size 1

Tools Required

- PS59/6/RGB—strip tool for mini coax
- CPLCCT-SLM—Compression Tool for connectors